



TORNADO

Surface Mounted 61 W Etanj LED Luminaire



Order Code : 3359379
Product Code : TRD 061U 400D00 9K72 150 66 HE ELP

Product Data

Standard Features


Housing	: Grey PC (high mechanical resistance, UV stability)
Diffuser	: Translucent PC with nanooptics (high mechanical resistance, UV stability)
IP Grade	: IP66
Installation	: Surface mounted
Light Source	: Mid Power LED
Electronic Control	: On/Off

Optical & Electrical Features

Power Consumption	: 59.9 W
Final Luminous Flux	: 9560.3 lm
Efficacy	: 159.4 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 50-60 Hz
Power Factor	: > 0,9
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

* There is $\pm 10\%$ tolerance in Technical Values

Photometric Curve



Other Features & Conditions

Operating Temperature Range	: -20 °C/+35 °C
Impact Resistance	: IK08
Led Life Time - L70	: > 102.000 hours @Ta= 35 °C

Optional Features

Correlated Color Temperatures	: 3000K, 5000K , 6500K
Emergency Kit Options	: 1, 3 hours



TORNADO

Surface Mounted 61 W Etanj LED Luminaire



3359379 TRD 061U 40OD00 9K72 150 66 HE ELP

Dimension (mm)

	a	b	h	d
Standard	1455	98	84	970-1230



1064641: TRD ASKI TAKIM KANCASI



- EAE, reserves the right to make changes without prior notice.