



TORNADO

Surface Mounted 39 W Etanj LED Luminaire

Order Code : 3270594
Product Code : TRD 039U 400D00 5K50 120 66 ELP



Product Data

Standard Features


Housing	: Grey PC (high mechanical resistance, UV stability)
Diffuser	: Translucent PC with nanooptics (high mechanical resistance, UV stability)
IP Grade	: IP66
Installation	: Surface mounted
Light Source	: Mid Power LED
Electronic Control	: On/Off

Optical & Electrical Features

Power Consumption	: 39.7 W
Final Luminous Flux	: 5556,6 lm
Efficacy	: 139,8 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 50-60 Hz
Power Factor	: > 0,9
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

* There is $\pm 10\%$ tolerance in Technical Values

Photometric Curve



Other Features & Conditions

Operating Temperature Range	: -25 °C/+35°C
Impact Resistance	: IK08
Led Life Time - L90B10	: > 102.000 hours @Ta= 35 °C

Optional Features

Correlated Color Temperatures	: 3000K, 5000K , 6500K
Emergency Kit Options	: 1, 3 hours



TORNADO

Surface Mounted 39 W Etanj LED Luminaire



3270594 TRD 039U 40OD00 5K50 120 66 ELP

Dimension (mm)

	a	b	h	d
Standard	1175	98	84	700-960



1064641: TRD ASKI TAKIM KANCASI



- EAE, reserves the right to make changes without prior notice.

EAE Aydınlatma A.Ş.
İkitelli Organize Sanayi Bölgesi Eski Turgut Özal Caddesi No:20 Başakşehir / İSTANBUL-TURKEY Phone: +90 212 413 21 00 (pbx) Fax: +90 212 549 37 90
www.eaeaydinlatma.com.tr