



STORM

SURFACE MOUNTED ADJ

20 W Spot LED Luminaire

Order Code : 3294786
Product Code : STO 020U 40SD00 40 2K4 ADJ FLP



Product Data

Standard Features


Housing	: Aluminium Injection Housing
Optic	: 40° Reflector
Ceiling Type	: Plasterboard
IP Grade	: IP20
Installation	: Surface Mounted
Light Source	: COB LED
Electronic Control	: On/Off

Optical & Electrical Features

Power Consumption	: 20 W
Final Luminous Flux	: 2420 lm
Efficacy	: 121 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 50-60 Hz
Power Factor	: Cos Ø > 0,9
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

* There is ± 10% Tolerance in Technical Values.

Photometric Curve



Other Features & Conditions

Operating Temperature Range	: -5 °C / +35 °C
Impact Resistance	: IK03
Led Life Time - L70	: 72.000 saat @Ta= 35 °C


Optional Features

Correlated Color Temperatures	: 2700K / 3000K / 6500K
Emergency Kit Options	: No
DALI Option	: Yes
Degree Option	: 24°

STORM SURFACE MOUNTED ADJ

20 W Spot LED Luminaire

3294786 STO 020U 40SD00 40 2K4 ADJ FLP



Dimensions (mm)

	a	b	h	Ø	Ø1
Standard	50	48	138	90	120

Weight (kg)

Standart	1.360
----------	-------



- EAE, reserves the right to make changes without prior notice.



EAE Aydınlatma A.Ş.
İkitelli Organize Sanayi Bölgesi Eski Turgut Özal Caddesi No:20 Başakşehir / İSTANBUL -TURKEY
Phone: +90 212 413 21 00 (pbx) Fax: +90 212 549 37 90
www.eaeaydinlatma.com.tr

Revision date: 11.03.2024