

BRICK

Recessed Mounted

Recessed Mounted 4 W Spot LED Luminaire

Order Code : 3160960
Product Code : ESP 004A 400A00 35 400 20 BR V.2 FLP



Product Data

Standard Features


Housing	: Aluminium housing
Diffuser	: 35° Reflector
IP Grade	: IP20
Installation	: Recessed mounted
Light Source	: COB LED
Electronic Control	: On/Off

Optical & Electrical Features

Power Consumption	: 4 W
Final Luminous Flux	: 439 lm
Efficacy	: 109,75 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 50-60 Hz
Power Factor	: Cos Ø > 0,9
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

* There is ± 10% Tolerance in Technical Values.

Photometric Curve



Other Features & Conditions

Operating Temperature Range	: -5 °C / +35 °C
Impact Resistance	: IK02
LED Life Time - L70	: > 50.000 hours @Ta= 35 °C

Optional Features

Correlated Color Temperatures	: 3000K / 6500K
DALI Option	: Yes
Degree Option	: 15° / 50°




BRICK Recessed Mounted

Recessed Mounted 4 W Spot LED Luminaire


3160960 ESP 004A 400A00 35 400 20 BR V.2 FLP

Dimensions (mm)

	a	b	h	d ¹ , d ²
Standard	90	90	103	73x73



- EAE, reserves the right to make changes without prior notice.



EAE Aydınlatma A.Ş.
İkitelli Organize Sanayi Bölgesi Eski Turgut Özal Caddesi No:20 Başakşehir / İSTANBUL-TURKEY Phone: +90 212 413 21 00 (pbx) F:
www.eaeaydinlatma.com.tr

Revision date: 24.03.2021