



OCTO V.2

30W LED Three-Phase Ray Spot Luminaire

Order Code : 3225820
Product Code : OCT 030F 40CM00 45 2K9 80 V.2 FLP

Product Data

Standard Features

Housing	: Aluminum injection housing, movable arm
Diffuser	: 45° reflector and glass
IP Grade	: IP 20
Installation	: Three-Phase Ray
Light Source	: COB LED
Electronic Control	: On/Off

Optical & Electrical Features

Power Consumption	: 30 W
Final Luminous Flux	: 2930 lm
Efficacy	: 97.6 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 50-60 Hz
Power Factor	: Cos Ø > 0,9
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80


* There is ± 10% Tolerance in Technical Values.

Other Features & Conditions

Operating Temperature Range	: -5 °C / +35 °C
Impact Resistance	: IK 02
Led Life Time - L70	: 60.000 saat @Ta= 35 °C



Photometric Curve




Optional Features

Correlated Color Temperatures	: 3000K, 6500K
Emergency Kit Options	: No
DALI Option	: Yes
Degree Option	: 15° / 30°

OCTO V.2

30W LED Three-Phase Ray Spot Luminaire

3225820 OCT 030F 40CM00 45 2K9 80 V.2 FLP



Dimensions (mm)

	Ø	a	h	h1
Three-Phase Ray	100	140	150	130

Weight (kg)

Three-Phase Ray	1,8
-----------------	-----



Rail Installation




①



②

① – ②

Key rail socket is inserted to
Three-phase - Single-phase Rail
in an oblique manner.



③




④

③ – ④

Locking catch on key rail socket is
turned as shown, then assembly
process is complete.

- EAE, reserves the right to make changes without prior notice.












EAE Aydınlatma A.Ş.

İkitelli Organize Sanayi Bölgesi Eski Turgut Özal Caddesi No:20 Başakşehir / İSTANBUL-TURKEY Phone: +90 212 413 21 00 (pbx) Fax: +90 212 413 21 01

www.eaeaydinlatma.com.tr

Revision date: 05.02.2021

ELECTROTRACK Ordering Table

Ordering Code	Descriptions	Product Codes	
3061351	1m SURFACE MOUNTED, GREY	TRIFAZE RAY 1MT.GRI.S.UST	
3061352	1m SURFACE MOUNTED, BLACK	TRIFAZE RAY 1MT.SIYAH.S.U	
3061350	1m SURFACE MOUNTED, WHITE	TRIFAZE RAY 1MT.BEYAZ.S.U	
3061356	2m SURFACE MOUNTED, BLACK	TRIFAZE RAY 2MT.SIYAH.S.U	
3061354	2m SURFACE MOUNTED, WHITE	TRIFAZE RAY 2MT.BEYAZ.S.U	
3061360	3m SURFACE MOUNTED, BLACK	TRIFAZE RAY 3MT.SIYAH.S.U	
3061359	3m SURFACE MOUNTED, WHITE	TRIFAZE RAY 3MT.BEYAZ.S.U	
3056387	1m RECESSED MOUNTED, WHITE	3FAZ.1M.S.ALT TRI.RAY BEY	
3056391	2m RECESSED MOUNTED, GREY	3FAZ.2M.S.ALT TRI.RAY GRI	
3056390	2m RECESSED MOUNTED, WHITE	3FAZ.2M.S.ALT TRI.RAY BEY	
3056393	3m RECESSED MOUNTED, WHITE	3FAZ.3M.S.ALT TRI.RAY BEY	
3081749	THREE-PHASE RAY SOCKET, GREY TRIFAZE RAY SOKETİ GRI		
3062139	THREE-PHASE RAY SOCKET, BLACK TRIFAZE RAY SOKETİ SIYAH		
3081748	THREE-PHASE RAY SOCKET, WHITE TRIFAZE RAY SOKETİ BEYAZ		
3056466	THREE-PHASE ENERGY INPUT, GRI ENERJİ GIRIŞ ADAPTOR GRI		
3056465	THREE-PHASE ENERGY INPUT, BLACK ENERJİ GIRIŞ ADAPTOR SIYAH		
3056464	THREE-PHASE ENERGY INPUT, WHITE ENERJİ GIRIŞ ADAPTOR BEYAZ		
3056282	3 PHASE LONG INTERTIE CONNecT 3 FAZ ARA BAĞL.N.UZUN.SIYA		
3056281	3 PHASE LONG INTERTIE CONNecT 3 FAZ ARA BAĞL.N.UZUN.BEYA		
3056410	3 PHASE INTERTIE CONNECTION, BLACK ARA BAĞLANTI ELEMANI SIYAH		
3056408	3 PHASE INTERTIE CONNECTION, WHITE ARA BAĞLANTI ELEMANI BEYAZ		
3056491	3 PHASE L CONNECTION, BLACK L 3 FAZ BAG. PARCASI SIYAH		
3056489	3 PHASE L CONNECTION, WHITE L 3 FAZ BAG. PARCASI BEYAZ		
3061346	3 PHASE T CONNECTION, WHITE T BAĞLANTI PARCASI BEYAZ		
3056284	3 PHASE ENDING COVER, GREY 3 FAZLI KAPAK SONLAND.GRI		
3056285	3 PHASE ENDING COVER, BLACK 3 FAZLI KAPAK SONLAND.SIY		
3056283	3 PHASE ENDING COVER, WHITE 3 FAZLI KAPAK SONLAND.BEY		
3056386	3 PHASE RAY CEILING CARRIER , 3 FAZLI RAY TAVAN TASIMCI		