




Recessed Mounted 84 W Spot LED Luminaire



Photometric Curve

Housing	: Aluminium Injection Housing
Optic	: 60° Reflector
Ceiling Type	: Plasterboard
IP Grade	: IP20
Installation	: Recessed Mounted
Light Source	: COB LED
Electronic Control	: On/Off



Power Consumption	: 84 W
Final Luminous Flux	: 9990lm
Efficacy	: 119 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 50-60 Hz
Power Factor	: Cos Ø > 0,9
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

* There is $\pm 10\%$ Tolerance in Technical Values.

Operating Temperature Range	: -5 °C / +35 °C
Operating Temperature Range With	: +5 °C / +35 °C
Emergency Kit	
Impact Resistance	: IK03
Led Life Time - L70	: 72.000 hours @Ta= 35 °C

Correlated Color Temperatures	: 2700K / 3000K / 6500K
Emergency Kit Options	: 1 / 3 hours
DALI Option	: Yes
Degree Option	: 24° / 40°



KRIZA 3X

Recessed Mounted 84 W Spot LED Luminaire

3236306 KRZ 084A 40SD00 60 10K0 3X V.2 FLP


Dimensions (mm)

	a	b	h	d1 X d2
Standard	155	410	120	390 x 140



Weight (kg)

Standart	4.050
----------	-------



- EAE, reserves the right to make changes without prior notice.

engineering the light

EAE Aydınlatma A.Ş.

İkitelli Organize Sanayi Bölgesi Eski Turgut Özal Caddesi No:20 Başakşehir / İSTANBUL-TURKEY

Phone: +90 212 413 21 00 (pbx) Fax: +90 212 549 37 90

www.eaeaydinlatma.com.tr

Revision date: 16.06.2023