



LORY FLAT IP65 KR

Recessed Mounted 15 W Spot LED Luminaire

Order Code : 3275130
Product Code : LRY 015A 40CM00 36 1K4 65 FL KR FLP



Product Data

Standard Features


Housing	: Aluminium Housing
Optic	: 36° Reflector
Ceiling Type	: Plasterboard
IP Grade	: IP65
Installation	: Recessed Mounted
Light Source	: COB LED
Electronic Control	: On-Off

Optical & Electrical Features

Power Consumption	: 14,7 W
Final Luminous Flux	: 1446,5 lm
Efficacy	: 98.4 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 50-60 Hz
Power Factor	: Cos Ø > 0,9
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

*There is ±%10 tolerance in the technical values.

Photometric Curve



Other Features & Conditions

Operating Temperature Range	: -5 °C / +35 °C
Operating Temperature Range With Emergency Kit	: +5 °C / +35 °C
Impact Resistance	: IK03
Led Life Time - L70	: 72.000 saat @Ta= 35 °C

Optional Features

Correlated Color Temperatures	: 2700K / 3000K / 6500K
Emergency Kit Options	: 1 / 3 Hours
DALI Option	: Yes
Degree Option	: 24° / 60°



LORY FLAT IP65 KR

Recessed Mounted 15 W Spot LED Luminaire

3275130 LRY 015A 40CM00 36 1K4 65 FL KR FLP

Dimensions (mm)

	a	b	h	øD
Standard	90	90	80	78






Weight (kg)

Standard



On-Off Driver / DALI Driver
IP65 Box

On-Off Driver / DALI Driver +
Emergency Kit IP65 Box



• EAE, reserves the right to make changes without prior notice.

engineering the light

EAE Aydınlatma A.Ş.

İkitelli Organize Sanayi Bölgesi Eski Turgut Özal Caddesi No:20 Başakşehir / İSTANBUL-TURKEY

Phone: +90 212 413 21 00 (pbx) Fax: +90 212 549 37 90

www.eaeaydinlatma.com.tr

Revision date: 10.07.2024