



## BELLA 2X

Recessed Mounted 12 W Spot LED Luminaire

Order Code : 3249381  
Product Code : BLL 012A 40SD00 36 1K3 20 2X FLP



### Product Data

#### Standard Features


Housing	: Aluminium housing
Optic	: 36° Reflector
Ceiling Type	: Plasterboard
IP Grade	: IP20
Installation	: Recessed mounted
Light Source	: COB LED
Electronic Control	: On-Off

#### Optical & Electrical Features

Power Consumption	: 12 W
Final Luminous Flux	: 1272 lm
Efficacy	: 106 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 50-60 Hz
Power Factor	: Cos Ø > 0,9
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

\*There is ±%10 tolerance in the technical values.

### Photometric Curve



#### Other Features & Conditions

Operating Temperature Range	: -5 °C / +35 °C
Operating Temperature Range With Emergency Kit	: +5 °C / +35 °C
Impact Resistance	: IK02
Led Life Time - L70	: 72.000 saat @Ta= 35 °C

#### Optional Features

Correlated Color Temperatures	: 2700K / 3000K / 6500K
Emergency Kit Options	: 1 / 3 hours
DALI Option	: Yes
Degree Option	: 24° / 60°



## BELLA 2X

### Recessed Mounted 12 W Spot LED Luminaire

3249381 BLL 012A 40SD00 36 1K3 20 2X FLP

#### Dimensions (mm)

	a	b	h	d <sup>1</sup> , d <sup>2</sup>
Standart	100	200	98	180x90



#### Weight (kg)

Standard	0.825
----------	-------



- EAE, reserves the right to make changes without prior notice.



Revision date: 01.11.2022