



BELLA 1X

Recessed Mounted 12 W Spot LED Luminaire

Order Code : 3249367
Product Code : BLL 012A 40SD00 36 1K3 20 1X FLP



Product Data

Standard Features


Housing	: Aluminium housing
Optic	: 36° Reflector
Ceiling Type	: Plasterboard
IP Grade	: IP20
Installation	: Recessed mounted
Light Source	: COB LED
Electronic Control	: On-Off

Optical & Electrical Features

Power Consumption	: 12 W
Final Luminous Flux	: 1272 lm
Efficacy	: 106 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 50-60 Hz
Power Factor	: Cos Ø > 0,9
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

*There is ±%10 tolerance in the technical values.

Photometric Curve



Other Features & Conditions

Operating Temperature Range	: -5 °C / +35 °C
Operating Temperature Range With Emergency Kit	: +5 °C / +35 °C
Impact Resistance	: IK02
Led Life Time - L70	: 72.000 saat @Ta= 35 °C

Optional Features

Correlated Color Temperatures	: 2700K / 3000K / 6500K
Emergency Kit Options	: 1 / 3 hours
DALI Option	: Yes
Degree Option	: 24° / 60°



BELLA 1X

Recessed Mounted 12 W Spot LED Luminaire

3249367 BLL 012A 40SD00 36 1K3 20 1X FLP

Dimensions (mm)

	a	b	h	d ¹ , d ²
Standart	100	100	98	90x90



Weight (kg)

Standard	0.380
----------	-------



- EAE, reserves the right to make changes without prior notice.



Revision date: 01.11.2022