



BISTA-K V.2-ADJ

Recessed Mounted 20 W Spot LED Luminaire

Order Code : 3236407
Product Code : BST 020A 40SD00 40 2K4 KR V.2 ADJ FLP



Product Data

Standard Features


Housing	: Aluminium injection housing
Diffuser	: 40° Reflector
Ceiling Type	: Plasterboard
IP Grade	: IP20
Installation	: Recessed mounted
Light Source	: COB LED
Electronic Control	: On/Off

Optical & Electrical Features

Power Consumption	: 20 W
Final Luminous Flux	: 2420 lm
Efficacy	: 121 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 50-60 Hz
Power Factor	: Cos ϕ > 0,9
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

* There is \pm 10% Tolerance in Technical Values.

Photometric Curve



Other Features & Conditions

Operating Temperature Range	: -5 °C / +35 °C
Operating Temperature Range With Emergency Kit	: +10 °C / +35 °C
Impact Resistance	: IK03
Led Life Time - L70	: 72.000 saat @Ta= 35 °C

Optional Features

Correlated Color Temperatures	: 2700 / 3000K / 6500K
Emergency Kit Options	: 1 / 3 hours
DALI Option	: Yes
Degree Option	: 24°



BISTA-K V.2-ADJ

Recessed Mounted 20 W Spot LED Luminaire

3236407 BST 020A 40SD00 40 2K4 KR V.2 ADJ FLP


Dimensions (mm)

	a	b	h	d1 x d2
Standard	137	137	165	124 x 124



Weight (kg)

Standart	1.380
----------	-------



- EAE, reserves the right to make changes without prior notice.

engineering the light

EAE Aydınlatma A.Ş.

İkitelli Organize Sanayi Bölgesi Eski Turgut Özal Caddesi No:20 Başakşehir / İSTANBUL-TURKEY

Phone: +90 212 413 21 00 (pbx) Fax: +90 212 549 37 90

www.eaeaydinlatma.com.tr

Revision date: 06.12.2022