



ORI SMALL

Recessed Mounted 12 W Spot LED Luminaire

Order Code : 3239109
Product Code : ORI 012A 40SD00 24 1K1 20 SML YV FLP



Product Data

Standard Features


Housing	: Aluminium Housing
Optic	: 24° Reflector
Ceiling Type	: Plasterboard
IP Grade	: IP20
Installation	: Recessed Mounted
Light Source	: COB LED
Electronic Control	: On/Off

Optical & Electrical Features

Power Consumption	: 12 W
Final Luminous Flux	: 1108 lm
Efficacy	: 92.3 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 50-60 Hz
Power Factor	: Cos Ø > 0,9
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

* There is ± 10% Tolerance in Technical Values.

Photometric Curve



Other Features & Conditions

Operating Temperature Range	: -5 °C / +35 °C
Impact Resistance	: IK03
Led Life Time - L70	: > 72.000 saat @Ta= 35 °C

Optional Features

Correlated Color Temperatures	: 2700K / 3000K / 6500K
Emergency Kit Options	: No
DALI Option	: Only (DALI version 6W-8W-10W)
Degree Option	: 36°



ORI SMALL

Recessed Mounted 12 W Spot LED Luminaire

3239109 ORI 012A 40SD00 24 1K1 20 SML YV FLP

Dimensions (mm)

	a	b	h
Standart	58	100	52



Weight (kg)

Standard	0.200
----------	-------

- EAE, reserves the right to make changes without prior notice.

engineering the light

EAE Aydınlatma A.Ş.
İkitelli Organize Sanayi Bölgesi Eski Turgut Özal Caddesi No:20 Başakşehir / İSTANBUL-TURKEY
Phone: +90 212 413 21 00 (pbx) Fax: +90 212 549 37 90
www.eaeaydinlatma.com.tr

Revision date: 30.01.2023