



STL-FLP RECESSED

20 W Recessed Mounted Single Module Linear LED Luminaire

Order Code : 3267106
Product Code : STL 020A 400D00 1K9 6770TK3I 60 FLP

Product Data

Standard Features

Housing	: Aluminium Extrusion Housing
Diffuser	: Opal Diffuser
IP Grade	: IP20
Installation	: Recessed Mounted
Light Source	: Mid Power LED
Electronic Control	: On/Off


Optical & Electrical Features

Power Consumption	: 20 W
Final Luminous Flux	: 1938,2 lm
Efficacy	: 96,91 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 50-60 Hz
Power Factor	: $\cos \phi > 0,9$
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

* There is $\pm 10\%$ Tolerance in Technical Values.



Photometric Curve



Other Features & Conditions

Operating Temperature Range	: -5 °C / +35 °C
Impact Resistance	: IK03
Led Life Time - L70	: 100.000 hours @Ta= 35 °C

Optional Features

Correlated Color Temperatures	: 2700K / 3000K / 6500K
Emergency Kit Options	: No
DALI Option	: Yes


STL-FLP RECESSED

20W Recessed Mounted Single Module Linear LED Luminaire

3267106 STL 020A 40OD00 1K9 6770TK3I 60 FLP

Dimensions (mm)

	a	b	h	h1	d ¹ , d ²
Single Module	617	67	70	100	604x54



Installation System


Module Model: Single (TK)



Single (TK)

Module Model: Starting (BS)

Module Model: Finishing (SN)



Starting (BS)

Finishing (SN)

Module Model: Starting (BS)

Module Model: Intermediate (AR)

Module Model: Finishing (SN)



Starting (BS)

Intermediate (AR)

Finishing (SN)

- EAE, reserves the right to make changes without prior notice.

engineering the light

EAE Aydınlatma A.Ş.
İkitelli Organize Sanayi Bölgesi Eski Turgut Özal Caddesi No:20 Başakşehir / İSTANBUL-TURKEY
Phone: +90 212 413 21 00 (pbx) Fax: +90 212 549 37 90
www.eaeaydinlatma.com.tr

Revision date: 23.03.2023