



CITY BOLARD

15 W Parks and Gardens LED Lighting Luminaire

Order Code : 3303345
Product Code : CTY 015Z 40CM00 1K0 66 BL 75 FLP



Product Data

Standard Features


Housing	: Aluminium Body (Chromate Coated)
Optic	: 4mm Glass
IP Grade	: IP66
Installation	: Floor Mounted
Light Source	: COB LED
Electronic Control	: On/Off

Optical & Electrical Features

Power Consumption	: 14.7 W
Final Luminous Flux	: 1043.7 lm
Efficacy	: 71 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 50-60 Hz
Power Factor	: Cos ϕ > 0,9
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

* There is \pm 10% Tolerance in Technical Values.

Photometric Curve



Other Features & Conditions

Operating Temperature Range	: -20°C / +45°C
Impact Resistance	: IK06
Led Life Time - L70	: > 60.000 hours @Ta= 45 °C

Optional Features

Correlated Color Temperatures	: 3000K / 6500K
Emergency Kit Options	: No
DALI Option	: Yes



CITY BOLARD

15 W Parks and Gardens LED Lighting Luminaire

3303345 CTY 015Z 40CM00 1K0 66 BL 75 FLP

Dimensions (mm)

	a	b	c	h
Standart	250	150	80	750



- EAE, reserves the right to make changes without prior notice.



EAE Aydınlatma A.Ş.
İkitelli Organize Sanayi Bölgesi Eski Turgut Özal Caddesi No:20 Başakşehir / İSTANBUL-TURKEY
Phone: +90 212 413 21 00 (pbx) Fax: +90 212 549 37 90
www.eaeaydinlatma.com.tr

Revision date: 5.06.2024