



BISTA-Y IP65 ADJ

Recessed Mounted 28 W Spot LED Luminaire

Order Code : 3296254
Product Code : BST 028A 40SD00 24 2K7 YV IP65 ADJ FLP



Product Data

Standard Features


Housing	: Aluminium Injection Housing
Diffuser	: 24° Reflector
Ceiling Type	: Plasterboard
IP Grade	: IP65
Installation	: Recessed Mounted
Light Source	: COB LED
Electronic Control	: On/Off

Optical & Electrical Features

Power Consumption	: 28 W
Final Luminous Flux	: 2653 lm
Efficacy	: 94.75 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 50-60 Hz
Power Factor	: Cos Ø > 0,9
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

* There is ± 10% Tolerance in Technical Values.

Photometric Curve



Other Features & Conditions

Operating Temperature Range	: -5 °C / +35 °C
Operating Temperature Range With Emergency Kit	: +5 °C / +35 °C
Impact Resistance	: IK03
Led Life Time - L70	: 72.000 saat @Ta= 35 °C

Optional Features

Correlated Color Temperatures	: 2700K / 3000K / 6500K
Emergency Kit Options	: 1 / 3 Hours
DALI Option	: Yes
Degree Option	: 40°



BISTA-Y IP65 ADJ

Recessed Mounted 28 W Spot LED Luminaire

3296254 BST 028A 40SD00 24 2K7 YV IP65 ADJ FLP


Dimensions (mm)

	Ø	h	ØD
Standard	140	165	124




Weight (kg)

Standart



Cut-out

Ø124



- EAE, reserves the right to make changes without prior notice.

engineering the light

EAE Aydınlatma A.Ş.

İkitelli Organize Sanayi Bölgesi Eski Turgut Özal Caddesi No:20 Başakşehir / İSTANBUL-TURKEY

Phone: +90 212 413 21 00 (pbx) Fax: +90 212 549 37 90

www.eaeaydinlatma.com.tr

Revision date:

30.05.2024