



FLEXBAR V.2

6 W/1m 7 Module LED Luminaire
Flexible Solution For Linear Lighting



Order Code : 3235173
Product Code : FLX 006G 40SD28 0K77 01M7 V.2

Product Data

Standard Features

Housing	: Plastic Injection
Diffuser	: Transparent diffuser
IP Grade	: IP20
Installation	: Cove lighting
Light Source	: Mid Power LED


Optical & Electrical Features

Power Consumption	: 5.6 W
Final Luminous Flux	: 763 lm (1 metre)
Efficacy	: 136.3 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 24V DC
Power Factor	: > 0,9
Max. Voltage Strength (Surge)	: 1 kV
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

Other Features & Conditions

Operating Temperature Range	: -20 °C/+45 °C
Operating Temperature Range With Emergency ACK	: +5 °C/+35 °C
Impact Resistance	: IK03
Led Life Time - L70	: > 102.000 hours @ Ta=45 °C

Photometric Curve




Optional Features

Correlated Color Temperatures	: 2700K, 3000K
Emergency Kit Options	: 1, 3 hours
DALI Option	: Yes

FLEXBAR V.2

6 W/1m 7 Module LED Luminaire Flexible Solution For Linear Lighting

3235173 FLX 006G 40SD28 0K77 01M7 V.2



Module Dimensions (mm)

	a	b	h
Standard	92	23	22

Weight (gr)


Standard	223
With Emergency Kit (1, 3 hrs.)	923, 1448

Opal Diffuser (Optional)



*Luminaire has halogen-free wiring.

Advantages



1m / 7 module

a: 71 mm

b: 144 mm

* Unit of measure between modules is mm.

*Ability to place 4, 5, 6, 7, 8, 9 modules per 1 m cable.

- EAE Aydınlatma reserves the right to make any change without prior notice.



Revision date: 31.10.2023