

BLOOM V3 IP65

Recessed Mounted 60x60cm 36 W LED Luminaire



Order Code : 3181655
Product Code : BLM 036A 40OD00 4K7606065 V.3

Product Data

Standard Features

Housing	: 0,60mm Recessed mounted RAL9003 Powder finished sheet steel
Diffuser	: Opal diffuser
Ceiling Type	: Plasterboard
IP Grade	: IP65
Installation	: Recessed mounted
Light Source	: Mid Power LED
Electronic Control	: On/Off

Optical & Electrical Features


Power Consumption	: 35.9 W
Final Luminous Flux	: 4833.3 lm
Efficacy	: 134.2 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 50-60 Hz
Power Factor	: > 0,9
Surge Transient Protection	: 1 kV
Drive Current	: 1050 mA
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80
Photobiological Risk Group	: RG0

* There is $\pm 10\%$ Tolerance in Technical Values.

Other Features & Conditions

Operating Temperature Range	: -20 °C/+40 °C
Operating Temperature Range With Emergency Kit	: +5 °C/+35 °C
Impact Resistance	: IK02
Led Life Time - L70	: > 102.000 hours @ Ta=40 °C

Photometric Curve




Optional Features

Ceiling Types	: Rock-wool, Clip-in
Correlated Color Temperatures	: 3000K, 6500K
Emergency Kit Options	: 1,3 hours
DALI Option	: Yes

BLOOM V3 IP65


Recessed Mounted 60x60cm 36 W LED Luminaire

3181655 BLM 036A 400D00 4K7606065 V.3




Dimensions (mm)

	a	b	h	d ¹ , d ²
Rock-wool	595	595	85	-
Plasterboard	633	633	85	610x610
Clip-in	600	600	85	-



Weight (kg)

Standard	7,5
With Emergency Kit (1 hr.)	9
With Emergency Kit (3 hrs.)	9,2



- EAE, reserves the right to make changes without prior notice.



Revision date: 12.04.2021