



SATURN V.E

Surface Mounted 16 W LED Lighting Luminaire

Order Code : 3175944
Product Code : STR 016U 400D00 1K4 65 V.E



Product Data

Standard Features

Housing	: Plastic housing
Diffuser	: Opal diffuser
IP Grade	: IP65
Installation	: Surface mounted
Light Source	: Mid Power LED


Optical & Electrical Features

Power Consumption	: 15.7 W
Final Luminous Flux	: 1406.1 lm
Efficacy	: 92 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 50-60 Hz
Power Factor	: > 0,9
Surge Transient Protection	: 1 kV
Drive Current	: 350 mA
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

Other Features & Conditions

Operating Temperature Range	: -20 °C/+35 °C
Operating Temperature Range With Emergency Kit	: 0 °C/+28 °C
Impact Resistance	: IK10
Led Life Time - L70	: > 72.000 hours @ Ta=35 °C

Photometric Curve




Optional Features

Correlated Color Temperatures	: 3000K, 5700K
Emergency Kit Options	: 1,3 hours
Sensor	: Yes (Detection Area 4x4m)
Dali	: Yes

SATURN v.E

Surface Mounted 16 W LED Lighting Luminaire

3175944 STR 016U 40OD00 1K4 65 V.E



Dimensions (mm)

	\varnothing	h
Standard	327,5	103



Weight (kg)

Standard	1,3
With Emergency Kit (1 hr.)	1,45
With Emergency Kit (3 hrs.)	1,45

- EAE Aydınlatma reserves the right to make any change without prior notice.



Revizyon tarihi: 27.06.2019